

Request for quotation

Safety mats SM and SM11

1/2

Submitted by

Company

Department

Surname

First name

Building number and street

Postcode

Town/city

Telephone

E-mail

i Having problems with some of the fields? Try opening the form in Acrobat instead.

Data transfer

We keep your personal data safe! All data is processed according to the statutory data protection regulations. We treat your data confidentially and do not pass it on to third parties. We will continue to store your data unless you ask us to erase it. For more information, please see our privacy policy. If you want us to erase your data, contact us at: datenschutz@mayser.com.

I consent to data transfer.

Area of application:

- Metalworking
- Injection moulding machinery
- Film extrusion
- Textile machinery
- Woodworking
- Other: _____

Ambient conditions

- Dry
- Water
- Oil
- Aggressive substances:
 - Coolant, type: _____
 - Solvent, type: _____
 - Other: _____
- Room temperature
- Other: from _____ °C to _____ °C

Electrical version:

NO contact

- /BK-type
- /W8k2-type
- With control unit _____

Cable ends:

- | | |
|---|--------------------------------------|
| Standard | Optional |
| <input type="checkbox"/> Wires stripped | <input type="checkbox"/> M8 plug |
| | <input type="checkbox"/> M8 coupling |

Cable length:

- | | |
|--|---|
| Without plug | With plug |
| <input type="checkbox"/> /W-type with 1 line
2.0 m (standard) | <input type="checkbox"/> 0.25 m (standard) |
| <input type="checkbox"/> /BK-type with 2 lines
2.0 m (standard) | <input type="checkbox"/> 1.0 m (standard) |
| <input type="checkbox"/> /BK-type with 1 line
2.0 m (standard) | <input type="checkbox"/> 0.25 m (standard) |
| Optional cable length: | <input type="checkbox"/> _____ m (max. 9.8 m) |
| <input type="checkbox"/> _____ m (max. 50 m) | |

Request for quotation

Safety mats SM and SM11

Dimensions:

Sensor max. 1.5 m² (width, depth: 200 to 3000 mm)

_____ × _____ mm
width × depth

Overall height, sensor surface, colour:

- 10 mm (SM **without** non-slip surface; grey)
- 15 mm**
SM with GM1
circular studs
 Black
 Yellow
- 19 mm**
SM with GM5
circular studs
Green
- 11 mm**
SM11
surface texture
Black

Fixing:

- | | | |
|---|--|--|
| <p>15 mm overall height</p> <ul style="list-style-type: none"> <input type="checkbox"/> Z-profile
on __ side(s) <input type="checkbox"/> AK 66
on __ side(s) <input type="checkbox"/> AK 105
on __ side(s) <input type="checkbox"/> Stepped hole AK 66 <input type="checkbox"/> Mitre cut | <p>19 mm overall height</p> <ul style="list-style-type: none"> <input type="checkbox"/> Z/1 profile
on __ side(s) <input type="checkbox"/> AK 105/1
on __ side(s) <input type="checkbox"/> Mitre cut | <p>11 mm overall height</p> <ul style="list-style-type: none"> <input type="checkbox"/> Z/2 profile
on __ side(s) <input type="checkbox"/> AP 45
on __ side(s) <input type="checkbox"/> AK 56
on __ side(s) <input type="checkbox"/> Stepped hole AK 56 <input type="checkbox"/> Outer corner connector
E1 <input type="checkbox"/> Inner corner connector
E2 <input type="checkbox"/> Connecting wedge Vk |
|---|--|--|

Area to be secured:

(Insert diagram here – including details of edge profiles and cable routing; alternatively, send CAD data together with the completed form)