

Request for quotation

SL NC II

1/2

Submitted by

Company

Department

Surname

First name

Building number and street

Postcode

Town/city

Telephone

E-mail

i Having problems with some of the fields? Try opening the form in Acrobat instead.

Data transfer

We keep your personal data safe! All data is processed according to the statutory data protection regulations. We treat your data confidentially and do not pass it on to third parties. We will continue to store your data unless you ask us to erase it. For more information, please see our privacy policy. If you want us to erase your data, contact us at: datenschutz@mayser.com.

☐ I consent to data transfer.

Area of application:

- ☐ Door or gate system
- ☐ Machinery or plant engineering
- ☐ Platforms or lifting devices
- ☐ Other: _____
- ☐ Finger detection required (only GP 48-2 NBR)

(Use not possible on closing edges with high levels of vibration)

Stopping distance s_1 :

max. _____ mm

← **this information is mandatory**

Alternative details:

Velocity v: max. _____ mm/s

Stopping time t_2 : max. _____ s

Installation position:

- ☐ A – Hanging down
- ☐ B – Standing upright
- ☐ C – Horizontal

(Installation position D – vertical not possible)

Electrical version:

Cable exit:

1 connection

2 connections

90° exit

☐ S1

☐ S2

Lateral exit

☐ SL

☐ SR

☐ SR2

Face

☐ ST1

☐ ST2

Sensor surface:

☐ EPDM

- Weatherproof
- Not oil-resistant
- Can be used down to -10 °C

☐ NBR

- Oil-resistant
- Use only above $+5\text{ °C}$
- Not weatherproof

Request for quotation

SL NC II

2/2

Rubber profile:

- ☐ GP 48-2 EPDM
- ☐ GP 65-2 EPDM
- ☐ GP 48-2 NBR
- ☐ GP 100-2 EPDM

Mounting:

- | Aluminium profile for | GP 48-2 | GP 65-2, GP 100-2 |
|--------------------------|--------------------------------|--------------------------------|
| Standard | ☐ C 26 | ☐ C 36 |
| Optional: | | |
| Two-part profile, type M | ☐ C 26M | ☐ C 36M |
| Flange profile, type S | | ☐ C 36S |
| Angle profile, type L | | ☐ C 36L |

Accessories:

- Extension kit

☐ 5 m (1003870)
- ☐ 10 m (1003871)
- Wiring aid

☐ Special resistor 1k2 (1003873)
- ☐ Special resistor 8k2 (1003874)

Area to be secured:

(Insert diagram here – including dimensions, or send CAD data together with the completed form)